

Express Workplace Cupboards



Sizes Available

Floor Versions:

1800Hx900Wx460Dmm - 3 shelves

900Hx900Wx460Dmm - 2 shelves



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound.

The product is powder-coated - Dark Blue RAL 5017 & Light Grey RAL 7035



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



Cupboard Construction

General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Delivered as a fully assembled unit.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.
- Fitted with "no snag" 2-point locking mechanism.
- Rust-resisting galvanised shelves – weight load of 50KG.
- The door aperture has return bends to eliminate open gaps.
- Additional shelves are available.



www.qmp.uk.com



01384 899800



sales@qmp.uk.com

Express Workplace Cupboards



Cupboard Construction

Door Construction:

- Material: 0.9mm Mild Steel
- A stiffener is spot-welded vertically in the centre of the door. Two 2½" butt hinges are spot welded to the door. The door is attached to the carcass via the hinges, with 4.8mm pop rivets. The door has two-point locking with an all-metal key-locking handle. A series of square holes 20mm x 20mm are punched in the door to create the perforation.



Replacement Locks & Spare Keys

Replacement locks and keys are available from QMP.
Replacement keys are available from Fast Key Ltd
www.fastkeys.co.uk - sales@fastkeys.co.uk.



5 Day Delivery

All sizes are available on our 5-day delivery service. Other sizes are available, however, on an extended lead-time.



Our live chat satisfaction rating,
based on user feedback



www.qmp.uk.com



01384 899800



sales@qmp.uk.com

