

Hazardous Cupboards



Sizes Available

Floor Versions:

- 1800Hx900Wx460Dmm - 3 shelves - 14-litre sump capacity.
- 1800Hx1200Wx460Dmm - 3 shelves - 18-litre sump capacity.
- 1200Hx900Wx460Dmm - 2 shelves - 14-litre sump capacity.
- 900Hx460Wx460Dmm - 1 shelf - 7-litre sump capacity.
- 900Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.
- 700Hx350Wx300Dmm - 1 shelf - 3-litre sump capacity.
- 700Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.

Mobile Versions:

- 1040Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.
- 840Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.

Floor Chest Versions:

- 610Hx1170Wx460Dmm - no shelf - 20-litre sump capacity.
- 510Hx610Wx340Dmm - no shelf - 7-litre sump capacity.

Wall-Mounted Version:

- 570Hx850Wx255Dmm - 1 shelf - no sump fitted.



Stickers supplied with our
Hazardous Cupboards



Paint Finish

A three-stage pre-treatment and phosphate coating are applied. Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound. The product is powder-coated - Truflow yellow.



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



www.qmp.uk.com



01384 899800



sales@qmp.uk.com

Hazardous Cupboards



Cupboard Construction

General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Integral liquid-tight sump fitted at the bottom of the cupboard (*except wall-mounted cupboard*).
- Door aperture has return bends to eliminate open gaps.
- Delivered as a fully assembled unit.
- Warning/hazardous labels supplied.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.
- Fitted with "no snag" 2-point locking mechanism.
- Adjustable spill-retaining galvanised shelves for superior spill management with a UDL of 50KG.

Floor Chest Construction:

- Material: 1.5mm mild steel.
- Fully welded integrated sump & angled lid to discourage article placement.
- Fully welded construction with 2 no. welded 2.5" butt hinges.
- Connected to the carcass with 4.8mm pop rivets.
- Fitted with restraint to prevent lid from falling back.
- Supplied with hasp and staple (padlock not supplied).



Replacement Locks & Spare Keys

Replacement locks and keys are available from QMP.

Replacement keys are available from Fast Key Ltd

www.fastkeys.co.uk - sales@fastkeys.co.uk.



5 Day Delivery

All sizes are available on our 5-day delivery service, except our Floor Chest Cupboards. This is a manufactured-to-order item and will be on an extended lead-time.



Our live chat satisfaction rating,
based on user feedback



www.qmp.uk.com



01384 899800



sales@qmp.uk.com

