

EASYSeal **Deck Protect**

Safer grip in the wet



3 litre ready-to-use bottle

Deck Protect uses the latest advances in chemical technology. It is a high-performance penetrating sealer, with the added bonus of improving foot traction to provide a safer grip on wet decking.

Using Deck Protect means there is no need to use grit or other abrasive coatings and there are no textural changes when dry. It will also assist in preserving the life of timber decking.

Features & Benefits

- Multiple actions in 1 Bottle
- Improves grip on wet timber flooring and decking
- Seals the wood yet allows it to "breathe"
- Excellent water proofing qualities
- Preserves the life of decking
- Resists algae and fungal growth
- Water based - contains no abrasives
- Invisible coating - no textural or long-term colour change
- Solvent free and easy to use

Coverage

- Up to 18m² for one coat depending on surface porosity

APPLICATION: DO NOT DILUTE - USE NEAT AS SUPPLIED

- SHAKE THE CONTAINER FOR 30 SECONDS BEFORE EACH USE
- Using a long pile roller or low-pressure sprayer, apply a generous even coat
- Mop-up any pooling before it dries
- Apply 1 or 2 coats depending on porosity. If liquid disappears from surface quickly, apply a 2nd coat within 1 hour of the first. Improved performance is achieved by applying subsequent coats 1 - 2 hours after the previous coat is touch dry
- Full performance is reached in 3 - 7 days depending on the timber

Precautions

- **Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish is acceptable**
- Do not use on a previously treated or painted surfaces
- Surface should be clean, dry, and free from mould, algae, and efflorescence before applying. If the surface has been cleaned prior to application, all traces of the cleaner must be removed with a pressure washer, as remaining residue could render the surface impermeable
- Ensure the surface is completely dry prior to application

- Keep children and pets/animals away until process is complete, and surface is dry
- Ideal operating temperature between 10°C and 20°C. As a guide ensure the surface is cool to touch
- Do not apply in damp/wet conditions or if rain is expected within 24 hours of application
- Do not apply during frost or when temperature is below 5°C. When used in cooler temperatures effectiveness may be reduced and longer drying time may be required

Aftercare

- Allow product to cure for 24 hours before subjecting to heavy use - increase this time in cold damp conditions
- Clean regularly with a non-abrasive cleaner to maintain the slip resistant properties of the treated surface
- Spillages or contaminants such as grease, oil, algae etc, should be removed immediately
- Re-treat with Deck Protect as necessary to maintain optimum performance
- Lightly used surfaces will last longer. Heavy traffic areas may need re-treating more frequently

Storage

- Store between 5°C and 25°C
- Store in a cool, well ventilated area
- Keep container tightly closed
- Keep out of direct sunlight and protect from frost in original container
- Keep out of reach of children

Health & Safety

- Do not eat, drink, or smoke when using this product
- Wear protective gloves/protective clothing/eye protection/face protection
- **IF ON SKIN:** Gently wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs seek medical advice/attention
- **IF IN EYES:** Bathe the eye with running water for 15 minutes. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Remove contact lenses if possible and safe to do so
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If feeling unwell, call for medical assistance

- MSDS sheet available by emailing info@azpects.co.uk

Version: 0325

azpects.co.uk

