

EASYSeal **Sandstone** **Enhancer & Sealer**

2-in-1 colour protector

5 litre ready-to-use bottle

A non-film forming sealer, designed to enhance the natural colours of sandstone paving without leaving a glossy finish.

Features & Benefits

- Enriches and enhances the natural tones of the paving
- Non-film forming for improved slip resistance
- Allows the stone to "breathe"
- Excellent oil and water repellent
- Superb anti-stain properties
- Resists cooking and engine oil, grease and fat
- Resists food and beverages including mustard, ketchup, most relishes, tea and coffee
- Good anti-graffiti properties
- Durable and long lasting
- Resists general dirt and grime
- Impedes moss and fungal growth
- Pressure washer resistant
- Environmentally friendly
- 100% water based - No toxic substances
- Can be used on damp surfaces
- Suitable for internal and external use

Coverage

- Up to 25m² for one coat depending on surface porosity. Deeper colours are obtained with two or more coats
- The finished appearance should be as if the surface is damp. This product does not give a full wet look. The full curing process takes up to 24 hours - longer in cold conditions. Coverage will vary dramatically according to the porosity of the paving

APPLICATION: DO NOT DILUTE - USE NEAT AS SUPPLIED

- SHAKE THE CONTAINER FOR 30 SECONDS BEFORE EACH USE
- Apply with a brush, roller, or sprayer
- For best results, we recommend that the product is applied using a low-pressure sprayer. Apply evenly but thoroughly and avoid "pooling". If necessary, clear excess by mopping with a damp cloth



Precautions

- **Always test on a small inconspicuous area to gauge how much sealer is required to reach desired level of enhancement**
- Sandstone Enhancer & Sealer is best applied on a dry surface but can be used on damp (not wet) paving. Do not apply if there is standing water
- Avoid applying if rain is predicted within 6 hours of application
- Ensure the paving is clean, sound, and dry. Surfaces should be free from any mould or fungal growth, waxes, or coatings
- Do not apply when surface temperatures are below 5°C or above 35°C
- Avoid foot traffic for 8+ hours after dry. Avoid vehicular traffic for 3 days
- Keep children and pets/animals away until process is complete and surface is dry

IMPORTANT INFORMATION REGARDING SURFACE TYPES.

- Textured (stippled) surfaces. This type of paving will not be protected on the top surface. This type of sealer will soak in and leave the tips of the paving in their natural state which aids slip resistance
- Do not apply to non-porous surfaces. Do not apply to painted surfaces or those that have been previously treated with silicone sealants or other water repellent materials
- If paving surface is smooth (polished), application is more difficult and may result in spotting or patches
- Depth of colours will be more evident when the surface has dried.
- We recommend that you consult our Technical Department before sealing these types of paving

Storage

- Store between 5°C and 25°C and keep container tightly closed.
- Keep container tightly closed
- Keep out of direct sunlight and protect from frost in original container
- Keep out of reach of children

Health & Safety

- Wear protective gloves/protective clothing/eye protection/face protection
- **IF ON SKIN:** Gently wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs seek medical advice/attention
- **IF IN EYES:** Bathe the eye with running water for 15 minutes. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Remove contact lenses if possible and safe to do so
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If feeling unwell, call for medical assistance

- MSDS sheet available by emailing info@azpects.co.uk

Version: 0325

azpects.co.uk

