

EASYPATIO JOINT REPAIR

Quick, *EASY*, and money saving patio joint repairs.



EASY Patio Joint Repair is a high-tech product for the renovation of failing mortar joints in patios and paths. It is a mixture of graded sand and special binders that is applied dry and activated with water. Once cured, it forms a strong, flexible joint that deters weeds and crawling insects.

An easy-to-use alternative to traditional mortar joints.

Usage - Ideal for areas of paving where existing mortar joints have failed in some areas and not others. **Save money by only repairing the sections that need it.**

Ready to use, *EASY* Patio Joint Repair allows for quick and easy jointing. It adheres to the sides of the paving without shrinking. It is resistant to erosion caused by water, frost, wind, cleaning, etc. Efflorescence-free.

Benefits

- Ready to use with no mixing required
- Suitable for use on all paving types*
- Simple to apply
- Activated by water - no portland cement
- No waste
- Strong & durable
- Resists weed growth**

How to use (protect eyes, skin & wear a face mask)

Areas for repair should be dry and free from loose debris and have a minimum depth of at least 20mm. Do not use below 10°C.

STEP 1: Open the tub and tip out enough material to fill the joint areas being repaired. Sweep the product into the joints until full. Gently firm the surface with a suitable tool and apply more product as required until the level of the joint is just below the surface of the paver.

STEP 2: Use a fine spray to wet the joints until no more water is absorbed. **CAUTION! DO NOT OVER-WATER.**

Joints should not be exposed to further wetting for at least 90 minutes after installation. The area can be walked on immediately but avoid disturbing the joints. Full strength is achieved after 30 days. To avoid any staining, a leaf blower is recommended to clear any fine sand particles off the surrounding paving before wetting, although this is not mandatory.

Storage

- The product should be stored in its original packaging, in a dry, well-ventilated place out of direct sunlight
- Keep container tightly closed and sealed until ready for use
- Containers that have been opened must be carefully resealed and kept upright to prevent leakage
- Shelf life: Unlimited if kept in optimum conditions

Disposal

- Dispose of contents and container in accordance with all local, regional, national and international regulations

Health & Safety

- Contains hydraulic cement
- May cause an allergic skin reaction
- Causes serious eye damage
- Wear protective gloves. Wear eye or face protection
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a **POISON CENTRE** or doctor

Consult MSDS for further information. Available by contacting info@azpects.co.uk

Disclaimer: This product is suitable for the intended use as described elsewhere on the label. However, the product's performance is directly linked to its application and use conditions, which must strictly adhere to following the instructions provided. Azpects has no control over surface preparation, application, and more generally the use of the product and as such cannot guarantee the finished work. Consequently, warranty is limited to the replacement of any defective product. Proof of purchase will be required for any claims. Before using this product, the user must ensure that the product is suitable for the intended use by conducting a test on a small area. The user alone assumes the risks associated with this use.

* Joint width must exceed 1.6mm

** Tap-root weeds will require removing/neutralising



Version: 0325